



THERAPY EQUIPMENT DIRECT DIAL FLOWMETER



**Direct Dial Flowmeter
in use**



**Direct Dial Flowmeter
with Humidifier**

The Direct Dial Flowmeter has been designed for attaching directly to the Medical Gas Pipeline Systems, generally in Wards.

It is capable of various flow ranges, according to the type purchased.

The Low Flow units are supplied with a Flush Rate (F) set at approximately 3LPM.

Advantages

- The Flow accuracy is guaranteed, and will always stay in calibration. It is recommended that the low flow units (0 - 1LPM and lower) be checked for accuracy annually.
- It has a holder for the mask and tubing, thus avoiding messy arrangements around the flowtube
- The tailpipe is a bayonet connection for easy fitting
- It can be used with various types of humidifier by means of an adaptor

Part Numbers

0 - 15LPM Model - (Settings: 0/1/2/3/4/5/6/7/8/10/12/15)	6560
0 - 1LPM Model - (Settings: 0/0.1/0.2/0.3/0.4/0.5/0.6/0.7/0.8/0.9/1.0/F)	6561
0 - 0.1LPM Model - (Settings: 0/0.01/0.02/0.03/0.04/0.05/0.06/0.07/0.08/0.09/0.10/F)	6562
0 - 0.25LPM Model - (Settings: 0/0.03/0.05/0.08/0.10/0.13/0.15/0.18/0.20/0.23/0.25/F)	6563
0 - 0.5LPM Model - (Settings: 0/0.05/0.10/0.15/0.20/0.25/0.30/0.35/0.40/0.45/0.50/F)	6564
0 - 2.5LPM Model - (Settings: 0/0.25/0.50/0.75/1.00/1.25/1.50/1.75/2.00/2.25/2.50/F)	6568

THE THERAPY EQUIPMENT LTD

UNIT 1, CRANBOURNE AVENUE
CRANBOURNE INDUSTRIAL ESTATE
POTTERS BAR, HERTS. EN6 3JN

TEL: 01707 652270 FAX: 01707 652622

E-mail: sales@therapyequipment.co.uk
Website: www.therapyequipment.co.uk



0086



FM 37970